EM-C1623

CUMMINS Engine



Generator Specification

| Service | PRP | ESP |
|----------------------|--------------|------|
| Power (kva) | 1475 | 1623 |
| Power (kw) | 1180 | 1298 |
| Rated speed (r.p.m) | 1500 | |
| Rated Power factor | 0.8 @lagging | |

Performance

| Engine Brand | CUMMINS | |
|-------------------------|-------------------|--|
| Engine model | KTA50-GS8/1287KW | |
| Alternator | VG-454C/1240KW | |
| Breaker | CHNIT MCCB 3P | |
| Control system | AMF digital panel | |
| Fuel consum. @100% load | 309 L/h | |



POWER

CERTIFICATE:

EMEAN Power gensets are compliant with ISO 9001 and CE standard, which include the following directives: EN ISO 12100:2010, EN ISO 8528-13:2016, EN 60204-1:2006+A1:2009+AC:2010, EN 55012:2007+A1:2009



CE

POWER DEFINITION:

PRP(Prime Power): Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP(Standby Power):The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1.Overload is not allowed


| Dimension | | |
|------------|--------|---------|
| Туре | Open | Silent |
| Length (L) | 5800mm | |
| Width (W) | 2010mm | 40HQ |
| Height (H) | 2500mm | |
| Net Weight | 9000kg | 11000kg |
| | | |

Standard Features:

- 1.power by Brand new water cooled diesel engine
- 2.Brushless alternators (Class H, with AVR)
- 3.Working condition: $0\,{}^\circ\!{\rm C}\,{\sim}\,{+}40\,{}^\circ\!{\rm C}$ (Antifreeze system needed if below $0\,{}^\circ\!{\rm C}\,{)}$
- 4.Base frame fuel tank for continue 8-10hrs running
- 5.Digital control panel with auto protection
- 6.MCCB air circuit breaker for over current shutdown
- 7.Industrial silencer for silent type generator sets 8.Humanized design, simple operation, easy maintenance
- 9.Ventilation parts are designed with modular principles
- 10.Soundproof canopy which lined with sound reducing foam
- 11.All metal canopy parts are painted by powder foam12.Glass Panel window
- 13.Lockable doors on front and back side for easy maintenance
- 14.Easy maintenance and operation
- 15.Easy lifting and moving, there is forklift hooks and crane holes on chassis
- 16.External emergency stop button
- 17.Steel chassis and anti-vibration pads
- 18.Includes diesel level sensor information to the controller


Warranty

We shall provide a warranty of 12 months or 1200 hours from B/L date (whichever comes first), covering all manufacturing defects. We replace damaged parts caused by manufacturing faults or defected parts/materials, but exclude the damageable parts due to customer's incorrect man-made operation. After expiration, we still provides technical and spare parts support with cost for maintenance.









CUMMINS KTA50-GS8/1287KW

Please download the detailed engine data sheet

Alternator VG-454C/1240KW

Please download the detailed alternator data sheet





Digital control panel (SMARTGEN brand HGM6120N)

Please download the detailed controller manual



AUTOMATIC SHUTDOWN AND FAULT CONDITIONS

- ·Under/over speed; fail to start
- ·High engine temperature; fail to stop
- ·Low oil pressure; charge fail
- ·Under/over generator volts; over current
- ·Under/over generator frequency; emergency stop
- ·Under/over mains frequency
- ·Under/over mains voltage
- ·Low/high battery volts

CHNIT MCCB breaker 3P



Sealed 12/24V Dry battery



Option



Contact Information

Email: sale5@fjepos.com

Phone: +86 19890349907

WHATSAPP



WECHAT



VIBER

